





- Engineered for the power and durability required for use with light gauge steel
- Accepts T-Nail style hardened trim pins
- Power to fasten to 14 ga steel at the speed of nailing to wood
- Operates using typical jobsite air compressor at 120 psi maximum
- Capable of driving pins 11/2" to 2-1/2" long
- Systems approach with tools and fasteners provides single source responsibility
- Comes standard with plastic carrying case



#### **CONTACT & SERVICE**

Our sales team is available at:

P +1 800 248 2376 F +1 440 248 0423 E etf@beck-fastening.com W www.beck-fastening.com

**PIN TYPE** AST-100 TRIMFAST<sup>®</sup> HEAVY DUTY TRIM PINS



# Trimfast<sup>®</sup> Heavy Duty Model 210

### **TOOL CHARACTERISTICS**

Height	Width	Length	Weight
12 inch	3 1/2 inch	11 1/2 inch	6 lbs
305 mm	89 mm	292 mm	2.72 kg

Pressure Lubricant 85 - 120 psi | 6 - 8 bar Non-detergent pneumatic tool lubricant

**Recommended steel thickness** 20 ga - 14 ga



wodel 210

# FASTENER DATA

Pin Type	AST-100-0150G	AST-100-0200G	AST-100-0250G		
Wire	0.086"   2.20 mm				
Shank	Smooth				
Head	1/4"   6 mm				
Length	1 1/2"   39 mm	2"   50 mm	2 1/2"   63 mm		
Coating	Electro Galvanized				
Magazine Capacity	50 pins				

#### **ACTUATION & LOADING**

Actuation System: Single sequential actuation

Loading: Magazine with latch

# **APPLICATIONS**

- James Hardie® XLD fiber cement trim to light gauge steel framing
- Miratec® treated exterior composite trim to light gauge steel framing
- Wood furring and exterior trim to light gauge steel framing
- Wood or metal furring to CMU

# **VERSION 09/2023 US**