



**F36 RHN33-38 DT
INVISIDECK**



**TOOL
FEATURES**

- Nose specially designed for perfect hold of I-CLP clips
- 3 - 5 times faster than conventional installation
- Saves time and labour costs

INVISIDECK® SCRAIL®

- **SCRAIL®** nail screw fasteners (33° plastic strip) for use with the **INVISIDECK®** tool
- 2.8 / 3.2 x 38 mm
- Fine thread
- Phillips drive
- **FASCOAT®**
- Black



CONTACT & SERVICE

Our sales team
is available at:

P +1 800 239 8665
sales@beck-america.com
www.beck-america.com

DESCRIPTION

Blind fastening systems are indispensable in modern decking installation. With the **INVISIDECK®** Hidden **SCRAIL®** system, decking can be installed with no visible or perceptible fasteners in a fifth of the time compared to traditional screw-fastening methods.



F36 RHN33-38 DT INVISIDECK

APPLICATIONS

- Hidden fastening decking on metal or wood substructure



HANDLING

1. Insert the clip into the decking board groove.
 2. Fix the clip to the joist with a **SCRAIL®** nail screw fastener.
 3. Place the next board on the clip.
- Steps 1 and 2 are done in one step with the INVISIDECK® installation tool. (see pictures)*

TOOL CHARACTERISTICS

Height	Width
285 mm	114 mm
11.20 inch	4.48 inch
Length	Weight
326 mm	2.30 kg
12.83 inch	5.00 lbs

Pressure

5,5 - 8 bar | 80 - 120 psi

Air consumption per shot

1.64 L. | 0.058 SCF

Performance at 90 psi | 6.2 bar
(0.62 MPa)

FASTENER DATA

Diameter	3.20 mm 0.125"
Length	38 mm 1 1/2"
Head	7 mm 0.275"
Nail Type	33° Plastic Strip SCRAIL® INVISIDECK®
Capacity	31
Clip	INVISIDECK® I-CLP, TC-G (TC-150)

NOISE VALUE

(EN 12549+A1 : 2008, EN ISO 4871 : 2009)

$L_{WA,1s}$: 92.00 dB (A) - $K_{WA,1s}$, 2.5

$L_{pA,1s}$: 105.00 dB (A) - $K_{pA,1s}$, 2.5

VIBRATION VALUE

(UNI ISO/TS 8662-11)

3.05 m/s²

ACTUATION & LOADING

Actuation System:

Single Shot

Loading: Rear Loading

INVISIDECK® I-CLP CLIP

Heavy gauge stainless steel clip for blind installation of grooved decking boards (25 mm or thicker).



INVISIDECK® SLOT CUTTER

The **INVISIDECK®** slot cutter allows you to prepare decking boards optimally for further processing with the **INVISIDECK®** Hidden **SCRAIL®** system. Usable as well as wood composites and hardwoods without grooves.

